

Apollo Paddle Pager

Hospitality Series



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com



P/N= **Paddle**

NOTE: Frequency Required when Ordered


Perfect for Restaurants and Waiting Rooms, etc.

Key Features:

- Synthesized or Crystal Type
- Tone / Vibration / Flash Only
- Flash with 6 LED Alert
- Two LED (Heartbeat, Alert, Out of Range and Low Battery)
- Rechargeable: Ni-MH Battery
- Over-the-Air "Off"
- Programmable Alert Modes
- Programmed by PC Software
- Advertising Insert
- Continuous Beep Option
- Out of Range Alert
- Low Battery Indicator
- Long Battery Life (Approx. 10 Days on 1 Single Charge)
- **Requires:** Charging Tray (Sold Separately) P/N= CHA02

Specifications:

- Model: AL-A02 (Also called the Paddle Pager)
- Frequency: 408-473 MHz and 138-174 MHz
- Paging Sensitivity: 512bps - 5 μ V/M, 1200bps - 7 μ V/M, 2400bps - 9 μ V/M
- Pager Baud Rate: 512 / 1200 / 2400bps for POCSAG,
- Channel Spacing: 25 KHz Wide Band (WB)
- Code Format: POCSAG
- Spurious Rejection: 40db below carrier
- Alert Tone Loudness: 85db @ 10 cm
- Cap Codes: 4 Cap Codes for POCSAG
- Weight: Approx. 108.5 Grams (w/o Battery)
- Dimension: 5.6(L) x 20.5(W) x 2.1(H) mm



Paddle-Pager Charging Tray
Charges 10 Pagers per Tray