

Apollo TE-505N Paging System

Hospitality Paging System



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= TE505N

NOTE: Frequency Required when Ordered

Key Features:

- POCSAG Transmitter
- Stand Alone / Desktop Model
- User Friendly Interface
- 15 Buttons
- Up to 999 Cap Codes
- Programmable by PC or by Keypad
- Backlit LCD Screen
- RS-232 Port: For PC Programming and Serial Data Input
- Hospitality Pagers: Works w / Coaster, Paddle and E-Pager
- Option: 5-watt Output - UHF RF Booster (TA-500)
P/N= 0119-1002

Specifications:

- Model: TE-505N for Hospitality (Tone Only) Pagers
- Paging Format: POCSAG
- Frequency: UHF 450-470 MHz and VHF 147-170 MHz
- Modulation Type: FSK
- Channel Spacing: 12.5 Narrow Band (NB)
- RF Output Power : 1 watt (5 watt Booster Available)
- Input Voltage: 8.4 v DC
- Current Consumption: Standby 120mA and TX 420mA
- Harmonic Radiation: Below -25 dbm
- Frequency Stability: 2.5 ppm at -10° C to 60° C
- Output Connect: BNC (F)
- Dimensions: 150 x 190 x 46 mm (w/o Ant.)
- Weight: Approximately 770g (w/o Antenna / Keyboard)