

Horn-Strobe Combo

For Annunciation when used with Wallpapers, PDR's and other Relay Triggered Devices



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= 0601-0119 When used with our RCD-1 PDR
P/N= 0601-0200 When used with AS-Series Signs

Federal Signal
STREAMLINE - Low Profile Combination Sounder/Strobe

Features:

- Fully Integrated Xenon Strobe Circuit
- Choice of 2 Different Tones
- Volume Output Adjustable for 20dB of Control
- Protection Rating IP 54, Type 4X
- Heavy Duty ABS Plastic Body
- CE Compliant
- Also Available with Optional Deeper Base allowing for 20mm Dia. Conduit Entry (**Special Order**)
- Removable Base for Mounting / Wiring

Specifications:

- Manufacturer Model: LP7 Sounder / Strobe
- Housing: White
- Dome: Red Color in Stock; All other Colors Available as Special Order
- Connection: Molex Connector
- **IMPORTANT:** When Ordering, Tell us which Device the Combo will be working with: **Sign or the RCD-1**
- Voltage: 24 Volts DC
Comes Wired and Ready with AC to DC Adaptor
- Flash Rate: 60 per Minute
- Sound Output: 82- 100 dB at 10' or 92- 110 dB at 1m
- Light Source: Strobe Tube
- Lamp Life: 10,000 Hours
- Mounting: Surface, Mounting Screw "Knock-outs" in Base of Enclosure (Screws Not Included)
- Wiring: Thru Existing ½ inch Hole in Center of the Base of Enclosure or thru a Drilled Hole in Side of Base Enclosure
- Dimensions: 3.66 inch Dia. X 3.5 inch Height

Tone Types:

- Tone #1: Sweeping Tone
or
- Tone #2: Continuous Tone