

Horn-Strobe Combo

For Annunciation when used with LED Signs, Wallpagers and other Relay Triggered Devices



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= 0601-0100 When used with our RCD-1 PDR
P/N= 0601-0118 When used with AS-Series Signs

Features:

- Multi-Tone Sounder in Combination with Xenon Flash
- Optical and Audible Signal can be Triggered Separately
- Choice of 8 Different Tones
- Adjustable Sound Output
- High Protection Rating IP 65
- Ready to Attach to WaveWare AS-122R LED Sign or to the WaveWare RCD-1 Paging Data Receiver
- Available in Red or Amber Colors Only (Specify at Order)
- Easy to Mount



Mount on AS-Series LED Signs (Shown)



Mount on Wall

Specifications:

- Model: 0601-0100, Integrated Horn/Strobe Kit
- Housing: Black
- Dome: Available in Red or Amber Only
- Connection: Molex Connector for RCD-1 or DB-9F for AS-Series Sign/Wallpager
- **IMPORTANT:** Use Proper Part Number for Correct Connector for use with AS-Series LED Sign or the RCD-1
- Voltage: 24 Volts DC
Comes Wired and Ready with AC to DC Adaptor
- Flash Frequency: 1 Hz
- Sound Output: 100 dB
- Mounting: Surface, Mounting Holes in Rim of Enclosure
- Dimensions: 89mm Dia. X 105mm H

Tone Types and Frequencies:

- Tone #1: Horn Tone
- Tone #2: Continuous Tone (ca. 2.3 KHz)
- Tone #3: 1 Hz Tone (c. 2.3 KHz)
- Tone #4: 20 Hz Whistle Tone (ca. 2.3 KHz)
- Tone #5: 800-970 Hz Rising @ 1 Hz
- Tone #6: 2400-2850 Hz Rising @ 7 Hz
- Tone #7: 1200-500 Hz Falling @ 1 Hz
- Tone #8: Alternating Tone 800 Hz to 1200 Hz @ 1 Hz