

CommTech MaxPage

Desktop Paging System



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



MaxPage P/N= 0114-1061

Product Features:

- **Manual Paging Methods:**
Built-in Numeric Keypad
Optional P/S-2 PC Keyboard (or Optional Windows Software)
- **External Keyboard: (Option)**
Any P/S-2 Compatible PC Keyboard
- **Reminder Messages:**
10 Reminder Messages
- **Function Keys:**
4 x Dual Mode Function Keys for Preconfigured Messages
- **Alarm Capacity:**
4 Alarm Inputs (Dry Contact Closure Type with Common Ground)
- **Alarm Programming:**
32 Character, Alphanumeric Message
Programmable Activation Delay
Call Escalation with Programmable Escalation Time Periods
- **PBX Interface: (Option)**
RJ-11, Two-Wire Analogue Extension (Voice Prompted)
- **PBX Messages:**
10 x User Defined Messages
- **RS-232 Serial Com Port: (Option)**
Supported Communication Protocols –
Scope, TAP, Comp 1 & Comp 2

MaxPage Specifications:

- **Internal Transmitter:**
2 or 5 watts
- **Frequencies:**
VHF: 138-170 MHz, UHF: 450-470 MHz
- **Supported Paging Protocols:**
POCSAG @ 512, 1200, and 2400 bps
- **Keypad:**
19 Numeric Backlit Silicon Keys
- **Recipient Capacity:**
9999 Pagers –
Tone, Numeric, Alphanumeric or Coaster Pagers
- **Group Capacity:**
20 Groups –
With any Combination of Recipients / Groups
- **LCD:**
2-Line x 16 Character Backlit LCD
- **Power Requirements:**
12-13.8 volt VDC at 2 A Regulated
- **Dimensions:**
360 x 220 x 86 mm (14 x 8.7 x 3.4 inches)
- **Weight:**
2.5kg / 5.5 lbs.

Note: The RS-232 Serial Com Port, the P/S-2 Keyboard and the PBX are ALL Options and **MUST** be purchased before they are activated.