

# WaveWare Paging Terminal

## 19" Rack Mount Paging Terminal



*"We Deliver Information at the Speed of Light"*

Visit Our Website at:

[www.WirelessMessaging.com](http://www.WirelessMessaging.com)



P/N= **PT1000KW**  
(100 watts)

### Key Features:

- WaveWare SPS-5 Series Paging Encoder Board
- Available with Our v9S, v9E or v9 Encoder ([Specify](#))
- Kenwood Repeater (19" Rack Mount Transmitter)
- 100 watt Amp (19" Rack Mount Amplifier)
- Rack Mount (Comes in a 19" Rack Enclosure, Shown)

### Compatible with:

- WaveWare Enterprise Messaging Software
- WaveWare Alert Utility Software
- WaveWare Call Manager Software
- Emergin / Philips / Rauland Systems
- Variety of Nurse Call, Alarm and Security Systems

### Specifications:

- Model: PT-1000-KW  
(PT-5000 Shown / PT-1000 is about 5 inches Taller)
- Transmitter: Kenwood Repeater - Model:  
TKR-850 UHF or TKR-750 VHF
- Enclosure: 19" Rack Enclosure
- Paging Format: POCSAG
- Working Frequency: UHF or VHF Factory Programmed
- Channel Spacing: 12.5 Narrow Band (NB)
- RF Output Power : 10- 40 watts UHF or 10-50 watts VHF
- RF Data Rate: 512 / 1200 / 2400 bps
- Serial Interface: TAP v1.8, COMP1, COMP2, Scope and  
WaveWare Paging Protocols
- Power Supply: Model SEC 1223-R1 – Rated 23 Amps  
13.8 v DC Output, 120v AC Input
- Pager Database: 5,000 Cap Codes, EEPROM  
Programmed with Windows Based Software (Included)
- Dimensions: Approx. 19 W x 19 H x 20 D inches
- Weight: Approx. 85 lbs. (w/o Antenna)

**Important:** For use as a **High Power** Paging Terminal  
Ordered as: 75 to 100 watts ([Specify](#))

**Requires:** **External Antenna Kit** (Sold Separately)  
P/N= 0007-1005 with 25 Ft. of Coax  
P/N= 0007-1006 with 50 Ft. of Coax  
Kits come with all Hardware required.

**NOTE:** [Specify Model Encoder when Pricing and Ordering](#)

**NOTE:** [Frequency Required when Ordered](#)