

WaveWare Paging Terminal

19" Rack Mount Paging Terminal



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= **PT5000KW**
(10-50 watts)

Key Features:

- WaveWare SPS-5 Series Paging Encoder Board
- Available with Our v9S, v9E or v9 Encoder ([Specify](#))
- Kenwood Repeater (Transmitter)
- Rack Mount (Comes in a 19" Rack Enclosure, Shown)

Compatible with:

- WaveWare Enterprise Messaging Software
- WaveWare Alert Utility Software
- WaveWare Call Manager Software
- Emergin / Philips / Rauland Systems
- Variety of Nurse Call, Alarm and Security Systems

Specifications:

- Model: PT-5000-KW
- Transmitter: Kenwood Repeater - Model: TKR-850 UHF or TKR-750 VHF
- Enclosure: 19" Rack Enclosure
- Paging Format: POCSAG
- Working Frequency: UHF or VHF
- Channel Spacing: 12.5 Narrow Band (NB)
- RF Output Power : 10- 40 watts UHF or 10-50 watts VHF
- RF Data Rate: 512 / 1200 / 2400 bps
- Serial Interface: TAP v1.8, COMP1, COMP2, Scope and WaveWare Paging Protocols
- Frequency Programming: Factory Programmed Only
- Power Supply: Model SEC 1223-R1 – Rated 23 Amps 13.8 v DC Output, 120v AC Input
- Pager Database: 5,000 Cap Codes, EEPROM Programmed with Windows Based Software (Included)
- Dimensions: Approx. 19 W x 15 H x 20 D inches
- Weight: Approx. 85 lbs. (w/o Antenna)

Important: Can be used for **Continuous "High Traffic"** Paging when used at 25 watts

Requires: **External Antenna Kit** (Sold Separately)
P/N= 0007-1005 with 25 Ft. of Coax
P/N= 0007-1006 with 50 Ft. of Coax
Kits come with all Hardware required.

NOTE: **Specify Model Encoder when Pricing and Ordering**

NOTE: **Frequency Required when Ordered**